

Optical Communications and Sensor Demonstration

Technologies for Proximity Operations and Data Transmission

The Optical Communications and Sensor Demonstration (OCSD) project addresses two cross-cutting capabilities of value to many future small spacecraft missions: high-speed optical transmission of data and small spacecraft proximity operations. Optical data rates demonstrated by OCSD are expected to be 200 megabits per second (Mb/s) or higher, a factor of 100 increase over current high-end CubeSat communications systems. The proximity sensors developed for this mission enable relative position measurement between two small satellites - a capability not previously demonstrated.

The OCSD project will produce three 1.5unit (1.5U) CubeSats that will be launched as secondary payloads on two separate missions. Each CubeSat is about 4 inches x 4 inches x 6.7 inches (10 centimeters x 10 centimeters x 17 centimeters) and weighs approximately 5 pounds (2.5 kilograms). The first OCSD mission, with one satellite, launched on Oct. 8, 2015 aboard an Atlas rocket from Vandenberg Air Force Base in California. This first OCSD flight was a risk reduction mission that allowed some checkout of the star trackers and important subsystems to include power, camera, GPS, radio and deployment mechanisms. It also allowed calibration and tool refinements to support the operational second flight of OCSD.

The second OCSD mission, with two satellites, is scheduled to launch no earlier than June 15, 2016, aboard a Falcon 9 rocket, also from Vandenberg. The satellites will be modified as necessary to incorporate the lessons learned during the first mission. For this second mission, laser communications system will be demonstrated in addition to the proximity operations demonstration, which will



OCSD Spacecraft Configuration

involve relative position measurements using cameras, beacons, laser rangefinders, and relative maneuvering using variable drag and propulsion. The novel propulsion system on OCSD uses water as a propellant, exhausted as steam.

The optical communications system on OCSD differs from other space-based laser communication systems because the laser is hard-mounted to the spacecraft body. The beam is pointed by controlling the orientation of the entire spacecraft. This makes the laser system much more compact than anything previously flown in space. The attitude control system developed for these satellites includes a pair of miniature star trackers that are devices that measure the position of stars for navigational purposes. These star trackers are expected to enable pointing to an accuracy of 0.05 degrees, which is 20 times the precision previously demonstrated in a satellite of this size.

The OCSD mission addresses the need for low-cost sensors that small spacecraft can use to assist in maneuvering and operating safely in close proximity to other spacecraft or objects in space. Capabilities in proximity operations will enable multiple

NASAfacts

small spacecraft to operate cooperatively during science or exploration missions, to approach another spacecraft or object for in-space observation or servicing, or to connect small spacecraft together to form larger systems or networks in space.

The potential for optical communications technology will not reach its limit with OCSD; it is anticipated that relatively simple upgrades, primarily to the attitude control system, will enable download rates of 2.5 gigabits per second (Gb/s) or higher. This would open the possibility of using small satellites in applications, such as synthetic aperture radar or hyperspectral Earth imaging, that produce volumes of data far beyond the capacity of radio-frequency downlink systems. It is also possible to use these satellites as data relay nodes in low-Earth orbit; a modest constellation of small satellites has the potential to provide low-latency, high-rate communications as a service for other satellites in orbit around Earth.

Demo:
Crosslink

Demo:
Proximity
Operations

Demo:
Uplink
5Mbits/s to
200Mbits/s

Santa Monica By
Mt-Wilson Observatory
Pasadena

The OCSD 1.5U CubeSat Transmits Data Via Laser from Space to Ground.

National Aeronautics and Space Administration

Ames Research Center Moffett Field, CA 94035

www.nasa.gov

The OCSD project is managed by The Aerospace Corporation of El Segundo, California.

The OCSD project is funded through NASA's Small Spacecraft Technology Program (SSTP), which is chartered to develop and mature technologies to enhance and expand the capabilities of small spacecraft with a particular focus on communications, propulsion, pointing, power, and autonomous operations. SSTP is one of nine programs within NASA's Space Technology Mission Directorate.

For more information about the SSTP, visit:

http://www.nasa.gov/smallsats

For more information about OCSD, please contact:

Richard Welle

Director, Microsatellite Systems Department The Aerospace Corporation Richard.P.Welle@aero.org

Roger C. Hunter

Small Spacecraft Technology Program Manager Space Technology Mission Directorate NASA Ames Research Center Roger.C.Hunter@nasa.gov

Andrew Petro

Small Spacecraft Technology Program Executive Space Technology Mission Directorate NASA Headquarters Andrew.J.Petro@nasa.gov